

QC STL PRO-2.5X RF
QuietCool Stealth Pro Line

QC TRI PRO-2.5X RF Specifications

Airflow	Hi: 2,490 CFM / Low: 1,934 CFM
HVI-916 Airflow (for CA Title 24 New Construction)	Hi: 1,800 CFM / Low: 1,370 CFM
Recommended SQFT Coverage @ 2-3 CFM per SQFT	Covers 830 SQFT to 1,245 SQFT
Energy Use	Hi: 244 Watts / Low: 198 Watts
Amps	Hi: 2.46 / Low: 1.89
Motor Voltage	120 VAC, 60 Hz
# of Speeds	2
dBA	Hi: 43.2 / Low: 37.4
Minimum Attic Clearance	34"
Duct Diameter	16"
Duct Length	6 feet
Motor Head Diameter	16 1/2"
Motor Head Length	13 1/2"
Dampers	Barometric Pressurized R5 Dampers
Controls	Included IT-36003 QuietCool Wireless RF Control Kit with Glass Wireless RF Switch
Warranty	Limited Lifetime
Framing	None Required
Joist Cutting	None Required; fits 16" or 24" on center
Minimum Suggested Attic Venting	3.32 SQ FT net free area
Ceiling Rough Opening	14 1/4" x 18 1/4"
Removable Grille Outside Dimension	16" x 20"
Shipping Weight	49 lbs.
Box Dimensions	24" x 20" x 38"
In The Box	-QC TRI PRO-2.5X Motorhead -Damper Box -Ceiling Grille -6 Foot Duct -Cut-out Template -Accessory Bag -Window Locks -Wireless RF Control Kit



For more information, visit our website at:
QUIETCOOLSYSTEMS.COM